



Colour and elegance meets speed and innovation.



print



colour

## Lexmark **C780n and C782n**

Everything you need to produce remarkable colour documents in-house!



- A4 colour laser printer
- Up to 38 ppm mono, 33 ppm colour
- Newly enhanced toner
- Robust design for high-volume printing

C780n

C780dn

C780dtn

C782n

C782dn

C782dtn

**LEXMARK**<sup>TM</sup>

# Lexmark C780n and C782n

Multiply the possibilities.



## Ride the wave of colour!

Colour is the future of office printing, and now Lexmark lets you get in on the action like never before! From memos and business reports to eye-catching catalogues, Lexmark's C780n and C782n laser printers give you everything you need to produce brilliant colour documents in-house. With our newly enhanced toner and long-term colour-science expertise, the results speak for themselves: crisp, professional-looking text, rich flesh tones and consistent images every time, from first page to last.

## Easier than ever to manage

What better way to boost productivity than by offering your employees a simple and secure new way of working? These printers are remarkably simple at every level, from set-up to maintenance. The front-loading consumables take just seconds to replace, while the intuitive operator panel coaches your end-users through printing and maintenance tasks with ease. And thanks to the cutting-edge security features with convenient numeric pad, you're always ensured true confidential printing.

# Lexmark C780 and C782n

## Serious performance for high-volume printing

Robust and reliable, the Lexmark C780n and C782n come network-ready and integrate seamlessly into your existing network environment. In virtually no time at all you'll be set up and running through your heaviest print jobs at record speeds! Besides their competitive time to first page, both printers are incredibly fast. So you can reduce the paper wait and get your documents in your hands faster.



## No worries – colour costs are under control!

The Lexmark C780n and C782n were designed to put you in total control of colour costs. In addition to high-yield cartridges and a low cost per page, both printers come equipped with Lexmark's unique ColorCare technology, a complete range of colour-cost-control tools. This includes convenient budget-friendly features, such as user-specific colour-print-permission settings, which let you limit which users can print in colour based on their specific job functions.

Which model is perfect for your needs?



### Lexmark C780n

- High-volume colour-laser printer
- Up to 33 ppm mono, 29 ppm colour
- 1,100-sheet maximum input capacity
- State-of-the-art security features



Model shown:  
Lexmark C782dtn

### Lexmark C782n

- Up to 40 ppm (38 ppm A4) mono, 35 ppm (33 ppm A4) colour
- 3100-sheet maximum input capacity
- Advanced finishing options available
- Upgradeable to a multifunction device

**Lexmark's guarantee to you :** At Lexmark, we're always working hard to ensure you maximum productivity and minimum downtime. C780n and C782n colour laser printers include our solid service guarantee of One-year On Site Repair, with a response time of next business day (in serviceable areas). For an even greater level of peace of mind, you can opt for one of our extended-guarantee service offerings. For more information on any of these offerings, just contact your local dealer or visit us today at [www.lexmark.com](http://www.lexmark.com).

# Lexmark C780n

## The high-performance answer to your high-volume colour needs

Easy to use, the Lexmark C780n lets you boost productivity with up to 33 ppm printing, and liven up your documents with brilliant colour output. It also comes equipped with a rich range of security and cost-control features.

### Print Technology

Color Laser

#### Print Speed (A4, Black)

Up to 33 ppm

#### Print Speed (A4, Colour)

Up to 29 ppm

#### Print Speed (Letter, Black)

Up to 35 ppm

#### Print Speed (Letter, Colour)

Up to 31 ppm

#### Time to First Page (Black)

As fast as 11 seconds

#### Time to First Page (Colour)

As fast as 13 seconds

#### Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

#### Print Resolution, Color

1200 x 1200 dpi, 4800 Color Quality

(2400 x 600 dpi)

#### Processor

800 / 133 MHz

#### Memory, Standard

256 MB

#### Memory, Maximum

768 MB

#### Expandable Memory Options

Yes

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0,

Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

#### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

#### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

#### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

#### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

#### Paper Handling Standard

250-Sheet Output Bin, 500-Sheet Input Tray, 100-Sheet Multipurpose Feeder

#### Paper Handling Optional

Duplex Unit, 500-Sheet Drawer

#### Paper Input Capacity (Standard)

600 pages 20 lb or 75 gsm bond

#### Paper Input Capacity (Maximum)

1100 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Standard)

250 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Maximum)

250 pages 20 lb or 75 gsm bond

#### Envelope Capacity

10

#### Finishing Option

No

#### Number of Paper Inputs

2

#### Number of Paper Inputs, Maximum

3

#### Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

#### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive,

Folio, JIS-B5, Legal, Letter, Statement, Universal

#### Connectivity (standard)

Fast Ethernet, One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

#### Connectivity (optional)

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8020 GigaBit Ethernet, Internal MarkNet™ N8050 802.11g Wireless, External MarkNet™ N7020e Gigabit Ethernet, Internal MarkNet™ N8030 Fiber Fast Ethernet

#### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services), Novell Netware Enterprise Print Services, Enhanced IP (Port 9400)

#### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™,

LexLink (DLC), TCP/IP IPv6

#### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

#### Printable Area

4.2 mm of the top, bottom, right and left edges (within)

#### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, PDF 1.5 Emulation, xHTML, Direct Image

#### Supplies Yield

Ships with 6,000\*-page black and colour Return Program Print Cartridges, 6,000\*-page (CMYK) Print Cartridges, 10,000\*-page (CMYK) High Yield Print Cartridges, \*Average continuous black or continuous composite CMY declared cartridge yield up to this # of standard pages in accordance with ISO/IEC 19798.

#### Packaged Size (mm - H x W x D)

810 x 795 x 650 mm

#### Size (mm - H x W x D)

528 x 604.5 x 470 mm

#### Weight (kg)

47.7 kg

#### Acoustics/Noise level (Idle mode)

30 dBA

#### Acoustics/Noise level (Operating mode)

52 dBA

#### Product Guarantee

One Year Onsite Repair

#### Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

#### Duty Cycle

Up to 120,000 (one-time monthly usage) Pages per month (one-time monthly usage)

#### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

# LEXMARK

# Lexmark C782n

## Extra speed and versatility for high-quality in-house printing

The Lexmark C782n gives you the quality, performance and versatility you need to produce all your important colour documents in-house. Expandable options include stackable input drawers, finishing, banner and outdoor media trays, and even a full upgrade to multifunction device.

### Print Technology

Color Laser

### Print Speed (A4, Black)

Up to 38 ppm

### Print Speed (A4, Colour)

Up to 33 ppm

### Print Speed (Letter, Black)

Up to 40 ppm

### Print Speed (Letter, Colour)

Up to 35 ppm

### Time to First Page (Black)

As fast as 11 seconds

### Time to First Page (Colour)

As fast as 13 seconds

### Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

### Print Resolution, Color

1200 x 1200 dpi, 4800 Color Quality

(2400 x 600 dpi)

### Processor

800 / 133 MHz

### Memory, Standard

256 MB

### Memory, Maximum

768 MB

### Expandable Memory Options

Yes

### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0,

Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

### Paper Handling Standard

250-Sheet Output Bin, 500-Sheet Input Tray, 100-Sheet Multipurpose Feeder

### Paper Handling Optional

5-Bin Mailbox, 650-Sheet Output Expander, StapleSmart Finisher, Duplex Unit, 500-Sheet Drawer, Envelope Drawer, Banner Media Tray, Outdoor Media Drawer, 2,000-Sheet High-capacity Feeder

### Paper Input Capacity (Standard)

600 pages 20 lb or 75 gsm bond

### Paper Input Capacity (Maximum)

3100 pages 20 lb or 75 gsm bond

### Paper Output Capacity (Standard)

250 pages 20 lb or 75 gsm bond

### Paper Output Capacity (Maximum)

900 pages 20 lb or 75 gsm bond

### Envelope Capacity

10

### Finishing Option

Yes

### Number of Paper Inputs

2

### Number of Paper Inputs, Maximum

5

### Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide, Outdoor Media, Banner Paper

### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Banner

### Connectivity (standard)

Fast Ethernet, One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

### Connectivity (optional)

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8020 GigaBit Ethernet, Internal MarkNet™ N8050 802.11g Wireless, External MarkNet™ N7020e Gigabit Ethernet, Internal MarkNet™ N8030 Fiber Fast Ethernet

### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400)

### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

### Printable Area

4.2 mm of the top, bottom, right and left edges (within)

### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, PDF 1.5 Emulation, xHTML, Direct Image

### Supplies Yield

6,000\*-page (CMYK) Print Cartridges, 10,000\*-page (CMYK) High Yield Print Cartridges, 15,000\*-page (CMYK) Extra High Yield Print Cartridges, Ships with 10,000\*-page black and colour High Yield Return Program Print Cartridges, \*Average continuous black or continuous composite CMY declared cartridge yield up to this # of standard pages in accordance with ISO/IEC 19798.

### Packaged Size (mm - H x W x D)

810 x 795 x 650 mm

### Size (mm - H x W x D)

528 x 604.5 x 470 mm

### Weight (kg)

47.7 kg

### Acoustics/Noise level (Idle mode)

30 dBA

### Acoustics/Noise level (Operating mode)

63 dBA

### Product Guarantee

One Year Onsite Repair

### Product Certifications

CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

### Duty Cycle

Up to 150,000 (one-time monthly usage)

Pages per month (one-time monthly usage)

### Specified Operating Environment

Temperature:

16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)



MFP  
upgradable



finishing  
optional



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

# LEXMARK

